



...for the long haul

HOUSE REMOVAL TRAILERS

ADAPTABLE

Built for KirkPatrick of USA, this trailer extends out to take a 20M Building. Built with TRT's unique Poly Beam & Torsional Box Trombone for a 40% improvement in stiffness over standard I Beam designs. With a lowered deck height of 900mm, raised deck height for this unit is 2,850mm. Other configuration trailers can achieve lowered deck heights from 750mm and a raised deck height from 1,650mm.

FLEXIBLE

The split axle fully independent suspension allows the lifting of any wheel set, giving the operator the flexibility to 'step over' obstacles, as shown on this trailer built for Davie Shoring and Moving USA. Designed to cope with difficult terrain on site, the whole trailer can be 'leant' on one side like this Craig Walker trailer, which enables trailer and load to negotiate a steep siding or to clear a bridge rail.

| Configuration | Lowered Deck Height | Raised Deck Height |
|----------------------|-------------------------|--------------------|
| 1.8 Mtr axle spacing | 900mm | 2,150mm |
| 2.4 Mtr axle spacing | 900mm | 2,850mm |
| SUPER LOW | 750 rear 500mm front | 1,650mm |



TRT (AUST) PTY. LTD.

www.tiddrosstodd.com

Australia: 1 800 802 912

New Zealand: 07 849 4839

Email: bcarden@trt.co.nz



...for the long haul

MANOEUVRABLE

Utilising BPW Steer axles converted by TRT to full hydraulic split axle power steer, provides 3 steering modes, castor steer, float steer, or hydraulically locked 'straight ahead'. Individual axle power steering is by Radio Remote. A LED indicator is fitted to show the driver when the axle is in the straight-ahead position.

TESTED

Prior to shipment and delivery, we test the fully independent suspension to ensure it operates through its wide range of movements. During road testing the steer axles are checked for response times and wheel alignment, both loaded and unloaded.

OPTIONS

Sideshift: Fitment of 3 sets of side shift legs will allow a 30T building to be moved 600mm sideways, ideal when splitting or joining a building.

Clip On: Extra capability can be added by attaching clip on modules to increase the number of axle lines.

King Pin Side Shift: Fitted to skid plate and operated via a compact double acting cylinder, this fitment allows very precise sideways movement to align the building on each pile. Makes high setting a building a breeze.



TIDD ROSS TODD LIMITED

www.trt.co.nz

New Zealand: 07 849 4839 | Australia: 1 800 802 912 | Email: bcarden@trt.co.nz