

# **Trailer Specifications**

## 2 x 4 Dolly

Drawing reference: 163-A1W

Forward Length 4.4m

Rear Overhang 1.2m

Width 2.4m

Axle Spacing 1.23m

ATM Rating 35 tonne

Tare 3,200 kg approx.

King Pin 2" or 3 ½" Jost Bolt up.

5<sup>th</sup> Wheel Fitted with a Semi oscillating - 5<sup>th</sup> wheel fitted with 2" or 3 ½" Jaws

**Skid Plate Height** To suit 5<sup>th</sup> wheel

**Skid Plate** Oscillator fitted.

Chassis Fabricated from Grade 80 Hi Tensile Plate.

**Suspension** Heavy duty mechanical spring suspension.

Axles 17.5", 10 stud drum braked axles with grease filled hubs.

Wheels 8 of 17.5 x 6.75 steel wheels.

**Tyres** 8 of 235 75R 17.5

**Spare Tyre Rack** Stowage for a total of up to 4 tyres. (17.5), complete with 2x J-Hook

kits.

**Guards** Plastic

**Braking** To meet ADR requirements.

**Lighting** LED lighting system.

Landing Legs Drop and pin RHS type

Paint Grit blasted, primed and painted in 2K paint system, electrostatically

applied for full coverage.

Please Note: Specifications shown above for New Zealand, please contact us for specification Australia and other countries.

#### **Trailer Options**

TRT has a wide range of standard and customisable options available for each trailer. These options are designed fit for purpose.

- Alloy wheels
- Guards alloy or stainless
- Spare wheel and tyre

#### Design and Engineering

TRT has a full range of design and build capability. If you require a transport solution or have a specific purpose for your new trailer, TRT are able to work with you from initial sketches or specifications to create fully engineered design solutions for your payloads now and in the future.

### Manufacturing

TRT design, fabricate and manufacture in house. TRT are accredited ISO 9001:2015, quality is critical to ensure your trailer will meet and in most cases exceed your requirements to minimise payback period. When you choose a trailer from TRT, it's for the long haul.



ADDRESS: 1028 Lytton Rd, Murarrie, QLD 4172
EMAIL: trailers@trtaust.com.au
WEB: www.trtaust.com.au